

American Standard® Commercial Gas Water Heaters

MODEL: D-100-250-AS 100 GALLON HEAVY DUTY STORAGE DIRECT SPARK IGNITION DAMPERED 250,000 BTU NAT GAS 250,000 BTU L.P. GAS




The American Standard Commercial Gas Model D-100-250-AS is designed to deliver large quantities of hot water economically through utilization of the most energy-saving techniques. Customary applications include industrial buildings, motels, hotels, schools, hospitals, restaurants, laundromats, car washes and multi-family developments up to sixteen single or twelve double bath units.

D-100-250-AS FEATURES

- Heavy Gauge Steel Tank incorporating only seven internal flue tubes resulting in fewer critical welds to yield added years of service.
- ASME Construction Model available.
- Inner tank glass-lined with Dura-Glas™ and fired at 1600° F for optimum protection from the effects of corrosion.
- R-8.3 non-CFC foam insulated to save energy and reduce fuel costs by maximizing heat retention.
- Four anode rods to ensure maximum tank life.
- Self-Cleaning turbulence inducing cold water inlet-tube engineered to diminish hard water area sediment deposits.
- Full size hand-hole cleanout for eased tank inspection and/or removal of sediment deposits.
- Electronic direct-spark ignition system saves fuel by eliminating the need for a standby gas pilot.
- Automatic motorized flue damper reduces tank heat loss during standby periods for lowest operating costs.
- Fully adjustable 24-volt controls provide temperature settings to 180° F. When installed with a mixing valve, the D-100-250-AS can deliver 180° F sanitizing and 140° F general purpose hot water simultaneously.
- Factory installed energy cut-off system and pressure/temperature valve.
- Top 1 1/2", 2" rear and 2" front water connections for universal replacements, connection to circulating lines and eased multiple heater or storage tank installations.
- AMERICAN STANDARD gas water heaters are certified at 300 PSI test pressure and for 150 PSI working pressure.
- Tested and listed with CSA International in accordance with ANSI Z21.10.3-CSA 4.3 for up to 180° F operation as an automatic storage and/or automatic circulating tank heater. Meets ASHRAE Standard 90.1-1999 and is NSF approved.
- Three year limited warranty on inner glass-lined tank and one year limited warranty on all other component parts.

THIS WATER HEATER MEETS THE REQUIREMENTS
OF ASHRAE 90.1-1999
AND MEETS OR EXCEEDS
THE THERMAL EFFICIENCY
AND STANDBY LOSS REQUIREMENTS
OF CALIFORNIA AND OTHER STATES
RECOGNIZING ASHRAE.

D-100-250-AS SPECIFICATIONS AND APPLICATION DATA



ELECTRICAL REQUIREMENTS
Need 120 Volt 60
Cycle AC Power
Draws less than 5 AMPS

SPECIFICATIONS

MODEL NUMBER*	TANK GALLONS CAPACITY	BTU INPUT NAT GAS	REC. GPH 100° RISE	BTU INPUT L.P. GAS	REC. GPH 100° RISE	THERM EFF %
D-100-250-AS	100	250,000	242	250,000	242	80%

*For ASME Model Specify D-100-250-ASME; for Propane (LP) Gas Model add suffix "LP"; for SCAQMD Low NOx Model add prefix "N"

DIMENSIONS SHOWN IN INCHES

EXTERIOR DIMENSIONS			V E N T	TOP PIPE SIZE	REAR & FRONT WATER CONN.	WATER I.P.S. CONNECTIONS (TOP, REAR & FRONT)				GAS I.P.S. CONN.		HGT TO TAP OPENING	TAP OPENING
A	B	C				HGT. TO TOP WATER	TOP WATER SPREAD	HGT. TO REAR & FRONT HOT	HGT. TO REAR & FRONT COLD	HGT	S I Z E		
73 ⁵ / ₈	30 ¹ / ₄	65 ⁵ / ₈	6	1 ¹ / ₂	2	D	E	F	G	H	J		
						67 ⁵ / ₈	23 ⁵ / ₈	57 ¹ / ₂	20	4 ³ / ₄	3/4	58 ⁷ / ₈	1

RECOVERY IN GALLONS PER HOUR AT VARIOUS TEMPERATURE RISES

MODEL NUMBER	GAS TYPE	BTU INPUT	TEMPERATURE RISE										
			40°	50°	60°	70°	80°	90°	100°	110°	120°	130°	140°
D-100-250-AS	NAT	250,000	606	485	404	346	303	269	242	220	202	186	173
	LP	250,000	606	485	404	346	303	269	242	220	202	186	173

MAXIMUM HOT WATER DELIVERABILITY AT VARIOUS TIME PERIODS

STORAGE CAPACITY U.S. GALLONS	ONE HOUR RECOVERY 100° RISE	1 ST HOUR	2 HOURS	3 HOURS	GPM REC. 100° RISE
100	242	312	554	796	4

Note: Recovery rate indicated on heater rating plate is based on 75% (76%) thermal efficiency according to CSA (ANSI, Z.21.10.3). Manufacturer reserves the right to make product changes and/or improvements with or without notice.

SAMPLE SPECIFICATION

Commercial gas water heater shall be AMERICAN STANDARD model _____ having a storage capacity of _____ gallons, operate on _____ Gas, with a BTU input of _____ and a recovery rate of _____ gallons per hour at 100° F temperature rise. Water heater tank interior shall be glass lined with Dura-Glas™, furnished with four anode rods and insulation shall be non-CFC foam of R-8.3. Water heater shall be CSA certified.



American Standard® Commercial Water Heaters

2808 Metropolitan Place, Pomona, CA 91767
1 (800)900-9063 • (909)392-0230 • Fax (909)392-7302