

# American Standard<sup>®</sup>

## Commercial Gas Water Heaters

### **MODEL: D-100T-199-AS (TALL)**

### **100 GALLON HEAVY DUTY STORAGE**

### **DIRECT SPARK IGNITION DAMPERED**

### **199,900 BTU NAT GAS**

### **199,900 BTU L.P. GAS**




The American Standard Commercial Gas Model D-100T-199-AS is designed to deliver large quantities of hot water economically through utilization of the most energy-saving techniques. Customary applications include industrial buildings, motels, hotels, schools, hospitals, restaurants, laundromats, car washes and multi-family developments up to fourteen single or eleven double bath units.

#### **D-100T-199-AS FEATURES**

- Heavy Gauge Steel Tank incorporating fewer internal flue tubes resulting in fewer critical welds to yield added years of trouble-free service.
- Inner tank glass-lined with Dura-Glas™ and fired at 1600° F for optimum protection from the effects of corrosion.
- R-8.3 non-CFC foam insulated to save energy and reduce fuel costs by maximizing heat retention.
- Four anode rods to ensure maximum tank life.
- Self-Cleaning turbulence inducing cold water inlet-tube engineered to diminish hard water area sediment deposits.
- Full size hand-hole cleanout for eased tank inspection and/or removal of sediment deposits.
- Electronic direct-spark ignition system saves fuel by eliminating the need for a standby gas pilot.
- Automatic motorized flue damper reduces tank heat loss during standby periods for lowest operating costs.
- Fully adjustable 24-volt controls provide temperature settings to 180° F. When installed with a mixing valve, the D-100T-199-AS can deliver 180° F sanitizing and 140° F general purpose hot water simultaneously.
- Factory installed energy cut-off system and pressure/temperature relief valve.
- Top 1½", 2" rear and 2" front water connections for universal replacements, connection to circulating lines and eased multiple heater or storage tank installations.
- AMERICAN STANDARD gas water heaters are certified at 300 PSI test pressure and for 150 PSI working pressure. All tanks are hydrostatically tested at the factory.
- Tested and listed with CSA International in accordance with ANSI Z21.10.3 - CSA 4.3 for up to 180° F operation as an automatic storage and/or automatic circulating tank heater. ASHRAE Standard 90.1 1999 addendum 90.1b. CSA certified to meet NSF/ANSI 5 Standards.
- Three year limited warranty on inner glass-lined tank and one year limited warranty on all other component parts.

THIS WATER HEATER MEETS THE REQUIREMENTS  
OF ASHRAE AND MEETS OR EXCEEDS THE  
THERMAL EFFICIENCY REQUIREMENTS  
OF CALIFORNIA AND OTHER STATES RECOGNIZING ASHRAE.

# D-100T-199-AS (TALL) SPECIFICATIONS & APPLICATION DATA



**ELECTRICAL REQUIREMENTS**  
Need 120 Volt 60  
Cycle AC Power  
Draws less than 5 AMPS

## SPECIFICATIONS

MODEL NUMBER	TANK GALLONS CAPACITY	BTU INPUT NAT GAS	REC GPH 100° RISE	BTU INPUT L.P. GAS	REC GPH 100° RISE	THERM EFF %
D-100T-199-AS	100	199,900	194	199,900	194	80%

\*For Propane (LP) Gas Model add suffix "LP"; For SCAQMD Low NOx Model add prefix "N"

## DIMENSIONS SHOWN IN INCHES

EXTERIOR DIMENSIONS	VENT	TOP PIPE SIZE	REAR & FRONT WATER CONN.	WATER I.P.S. CONNECTIONS (TOP, REAR & FRONT)				GAS I.P.S. CONN.		HGT TO T&P OPENING	T&P OPENING		
				HGT. TO TOP WATER	TOP WATER SPREAD	HGT. TO REAR & FRONT HOT	HGT. TO REAR & FRONT COLD	HGT	SIZE				
A	B	C		D	E	F	G	H		J			
78 1/4	28 1/4	70 1/2	6	1 1/2	2	73 5/8	21 1/4	62	18 3/4	4 3/4	3/4	63 5/8	3/4

## RECOVERY IN GALLONS PER HOUR AT VARIOUS TEMPERATURE RISES

MODEL NUMBER	GAS TYPE	BTU INPUT	TEMPERATURE RISE										
			40°	50°	60°	70°	80°	90°	100°	110°	120°	130°	140°
D-100T-199-AS	NAT	199,900	485	388	323	277	242	215	194	176	162	149	138
	LP	199,900	485	388	323	277	242	215	194	176	162	149	138

## MAXIMUM HOT WATER DELIVERABILITY AT VARIOUS TIME PERIODS

STORAGE CAPACITY U.S. GALLONS	ONE HOUR RECOVERY 100° RISE	1 <sup>ST</sup> HOUR	2 HOURS	3 HOURS	GPM REC. 100° RISE
100	194	264	458	652	3.2

Note: Recovery rate indicated on heater rating plate is based on 75% (76%) thermal efficiency according to CSA (ANSI, Z.21.10.3). Manufacturer reserves the right to make product changes and/or improvements with or without notice.

## SAMPLE SPECIFICATION

Commercial gas water heater shall be AMERICAN STANDARD model \_\_\_\_\_ having a storage capacity of \_\_\_\_\_ gallons, operate on \_\_\_\_\_ Gas, with a BTU input of \_\_\_\_\_ and a recovery rate of \_\_\_\_\_ gallons per hour at 100° F temperature rise. Water heater tank interior shall be glass lined with Dura-Glas™, furnished with four anode rods and insulation shall be non-CFC foam of R-8.3. Water heater shall be CSA certified.



*"Living Up to A Higher Standard"*

**American Standard® Commercial Water Heaters**

2808 Metropolitan Place • Pomona • CA 91767

1 (800) 900-9063 • (909) 392-0230 • Fax (909) 392-7302