

American Standard®

Commercial Gas Water Heaters

MODEL: D-75-399-AS

75 GALLON HEAVY DUTY INSTANTANEOUS DIRECT SPARK IGNITION DAMPERED

399,900 BTU NAT GAS

399,900 BTU L.P. GAS



The American Standard Commercial Gas Model D-75-399-AS is designed to deliver large quantities of hot water economically through utilization of the most energy-saving techniques. Customary applications include industrial buildings, motels, hotels, schools, hospitals, restaurants, laundromats, car washes and multi-family developments up to 24 single or 17 double bath units.

D-75-399-AS FEATURES

- Heavy Gauge Steel Tank utilizes only twelve internal flue tubes resulting in fewer critical welds to yield added years of trouble-free service.
- ASME Construction Model available.
- Inner tank glass-lined with Dura-Glas™ and fired at 1600° F for optimum protection from the effects of corrosion.
- R-8.3 non-CFC foam insulated to save energy and reduce fuel costs by maximizing heat retention.
- Four anode rods to prolong tank life.
- Self-Cleaning turbulence inducing cold water inlet-tube engineered to diminish hard water area sediment deposits.
- Full size hand-hole cleanout for eased tank inspection and/or removal of sediment deposits.
- Electronic direct-spark ignition system saves fuel by eliminating the need for a standby gas pilot.
- Automatic motorized flue damper reduces tank heat loss during standby periods for lowest operating costs.
- Fully adjustable 24-volt controls provide temperature settings to 180° F. When installed with a mixing valve, the D-75-399-AS can deliver 180° F sanitizing and 140° F general purpose hot water simultaneously.
- Factory installed energy cut-off system and pressure/temperature relief valve.
- Two inch rear and front water connections for simplified replacement of similar units, connection to circulating lines and eased multiple heater or storage tank installations. CSA certified to meet NSF/ANSI 5 Standards.
- AMERICAN STANDARD gas water heaters are certified at 300 PSI test pressure and for 150 PSI working pressure. All tanks are hydrostatically tested at the factory.
- Tested and listed with CSA International in accordance with ANSI Z21.10.3 - CSA 4.3 for up to 180° F operation as an instantaneous and/or automatic circulating tank heater. Meets ASHRAE 1992 90.1b.
- Three year limited warranty on inner glass-lined tank and one year limited warranty on all other component parts.

THIS WATER HEATER MEETS THE REQUIREMENTS
OF ASHRAE 1992 STANDARD ADDENDUM
90.1b AND MEETS OR EXCEEDS THE THERMAL
EFFICIENCY AND STANDBY LOSS REQUIREMENTS
OF CALIFORNIA AND OTHER STATES
RECOGNIZING ASHRAE.

D-75-399-AS SPECIFICATIONS AND APPLICATION DATA


SPECIFICATIONS

MODEL NUMBER*	TANK GALLONS CAPACITY	BTU INPUT NAT GAS	REC GPH 100° RISE	BTU INPUT L.P. GAS	REC GPH 100° RISE	THERM EFF %
D-75-399-AS	75	399,900	393	399,900	393	81%

*For ASME Model: Specify D-75-399-ASME; For Propane (LP) Gas Model add suffix "LP"; For SCAQMD Low NOx Model add prefix "N"

DIMENSIONS SHOWN IN INCHES

EXTERIOR DIMENSIONS			V E N T	REAR & FRONT WATER CONN. SIZE	WATER I.P.S. CONNECTIONS (REAR & FRONT)		GAS I.P.S. CONN.		H G T TO T&P O P E N I N G	T&P O P E N I N G
A	B	C			HEIGHT TO REAR & FRONT HOT	HEIGHT TO REAR & FRONT COLD	H G T	S I Z E		
75 ³ / ₄	30 ¹ / ₄	66 ¹ / ₄	8	2	57	19 ¹ / ₄	4 ³ / ₄	3/4	58 ¹ / ₄	1



ELECTRICAL REQUIREMENTS
Need 120 Volt 60
Cycle AC Power
Draws less than 5 AMPS

RECOVERY IN GALLONS PER HOUR AT VARIOUS TEMPERATURE RISES

MODEL NUMBER	GAS TYPE	BTU INPUT	TEMPERATURE RISE										
			40°	50°	60°	70°	80°	90°	100°	110°	120°	130°	140°
D-75-399-AS	NAT	399,900	982	785	654	561	491	436	393	357	327	302	280
	LP	399,900	982	785	654	561	491	436	393	357	327	302	280

MAXIMUM HOT WATER DELIVERABILITY AT VARIOUS TIME PERIODS

STORAGE CAPACITY U.S. GALLONS	ONE HOUR RECOVERY 100° RISE	1 ST HOUR	2 HOURS	3 HOURS	GPM REC. 100° RISE
75	393	446	839	1,232	6.6

Note: Recovery rate indicated on heater rating plate is based on 75% (76%) thermal efficiency according to CSA (ANZI, Z. 21.10.3). Manufacturer reserves the right to make product changes and/or improvements with or without notice.

SAMPLE SPECIFICATION

Commercial gas water heater shall be AMERICAN STANDARD model _____ having a storage capacity of _____ gallons, operate on _____ Gas, with a BTU input of _____ and a recovery rate of _____ gallons per hour at 100° F temperature rise. Water heater tank interior shall be glass lined with Dura-Glas™, furnished with four anode rods and insulation shall be non-CFC foam of R-8.3. Water heater shall be CSA certified.



American Standard® Commercial Water Heaters

2808 Metropolitan Place, Pomona, CA 91767

1 (800)900-9063 • (909)392-0230 • Fax (909)392-7302